

Araldite KladX

Jaldi se mazboot jod

Fast-setting adhesive for heavy duty stone cladding using spot bonding

Araldite® Builder Klad-X is a two-component room temperature curing epoxy adhesive for Construction Applications



Key Features



Easy to apply through Spot Bonding



Fast Setting within 30 to 40 mins allowing quick removal of support



10X stronger than concrete



Underwater curing



Compatible with Multiple Substrates

Other Features

- Bond Strength (LSS) - > 100 kg/ sq.cm
- Load bearing Capacity - 500 to 750 kg
- Pot life - 10 to 12 Mins
- **Coverage**
 - 100 sq. ft./1.5 kg set in spot bonding covering with blobs of 3 mm thickness.
 - 9 to 10 Sq. ft. with bed thickness of 1 mm.
- Mixing Ratio by volume of Resin & Hardener is 2 : 1

Application Areas



Cladding applications



Overhead applications



Lift Lobby




Low contact surface area application




How to apply




Ensure that the marble / granite slab and wall are smooth, even and dust free



Mix Part A and B in 2:1 ratio by volume and use within 10 to 12 minutes



Apply a thick blob of the mixture at corners and centre or apply a thin layer evenly on entire surface of slab



Stick the slab to the dry surface and provide support for 30 to 40 minutes