

TILE & STONE EPOXY ADHESIVE RANGE

Araldite KLAD PRO

Stone Cladding ka Pro

A high-performance, multipurpose, adhesive for fixing all types of tiles & stones including composites, engineered/ nano stones, metal & glass tiles on interior and exterior floor & wall.

FEATURES

- Multi-Substrate
- High Flexibility
- High Open Time
- Ideal for light coloured stones

MORE DETAILS

- Suitable for High Vibration Areas
- Used on Internal and External Areas
- PU Epoxy Hybrid adhesive
- Low VOC
- Coverage:
 - 16 - 20 sq. ft/ 4 kg pack - 1.5 mm bed thickness (using 3 mm x 3 mm notch).
 - 8 - 10 sq. ft/ 4 kg pack - 3 mm bed thickness (using 6 mm x 6 mm notch).


HOW TO APPLY



The substrate should be sound & thoroughly cleaned & free from loose particles, wax, grease, moss, polish etc.



Mix Hardener (B) thoroughly with Base (A) already present in the Pail as per preset ratio



Always mix a required quantity which can be consumed within 90 minutes pot life at 30°C



Spread the adhesive to a required bed thickness & comb it with a notch trowel



Apply the adhesive paste which can be applied within 60 minutes (at 30°C). Apply firm pressure to ensure better coverage on the back of the stones



Allow the stone to set for 24 hours



AVAILABLE IN: 4 kg



PU Epoxy Hybrid technology-based, adhesive that is flexible and can be used on multiple substrates with high undulations

APPLICATION AREAS



Metal Cladding



Stone Cladding



TV Units



Home Interiors