

Araldite Klear 20

Na sookhne ka darr, lagaiye befikar

Fast & Clear Epoxy for application on larger surface areas

Araldite® Klear 20 is a Fast & Clear Epoxy for application in larger surface areas.

It is suitable for bonding a variety of Glass, Stone, Wood, Metal, Ceramic, Rubber, Dry Concrete, Asbestos, Cement & Bison board, Fabric, Leather & most rigid Plastics.



Key Features



Ideal Pot life of 10 to 15 minutes giving the user enough time to work on medium to large surfaces.



Setting time of 20 mins leading to time saving and faster completion of work



High Clarity



Multi-Substrate



High bond strength

Other Features

- Bond Strength (LSS) - > 100 kg/ sq.cm
- Load bearing Capacity - 290-300 kg
- Pot life - 10 to 15 Mins
- Coverage - 100 to 110 sqft. /1.8 kg set (with 0.4 to 0.5mm Adhesive thickness)
- Mixing Ratio by vol. 1 : 1

Application Areas



Kitchen Platform



Marble Shelves



Glass Furniture



Staircase




Available in: 250g, 450g, 1kg, 2kg


How to apply



Roughen, degrease & dry surfaces to be bonded



Mix equal Volume of Resin & Hardener; Use the mix within 10 to 15 minutes



Apply thin layer on both surfaces and clamp joint for 20 minutes