

Araldite Klear 5

Kwik bhi, Klear bhi

Fast & Clear epoxy for application on wide variety of substrates

Araldite® Klear 5 is a two component, rapid curing transparent epoxy used to bond a variety of substrates.

It is suitable for bonding a wide variety of Glass, metals, Stone, Wood, Ceramic, Rubber, Dry Concrete, Asbestos, Cement & Bison board, Fabric, Leather & most rigid Plastics.



Key Features



5 Mins Fast Setting



Transparent glue line



Compatible with Multiple Substrates



Odourless

Other Features

- Bond Strength of Klear 5 with
 - Metals - 112 kg/cm²
 - Glass - 71 kg/cm²
- Load Bearing Capacity - 357 kg
- Pot life - 2 to 3 Mins
- Mixing Ratio by volume 1 : 1

Application Areas



Edge banding of kitchen platforms



Shelves



Artificial jewelry




Name plates on walls

Available in: 5g, 10g, 26g, 90g, 180g, 270g, 450g, 1.08kg


How to apply



Roughen, degrease & dry surfaces to be bonded



Mix equal Volume of Resin & Hardener; Use the mix within 2 to 3 minutes



Apply thin layer on both surfaces and clamp joint for 5 minutes

Klear 5	VS	Competition
HIGHER COVERAGE 	COVERAGE 	LOWER COVERAGE
25% MORE BOND STRENGTH 	BOND STRENGTH 	LESS BOND STRENGTH
100% CLEAR 	APPEARANCE 	HAZY